


SLP120-12

High Efficiency Multicrystalline PV Module

Electrical Characteristics	SLP120-12
Produc code	120011203A
Maximum power (Pmax)	120W
Voltage at Pmax (Vmp)	17.2V
Current at Pmax (Imp)	6.98A
Open-circuit voltage (Voc)	21.6V
Short-circuit current (Isc)	7.72A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/°C
Temperature coefficient of power	-(0.5±0.05)%/ °C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%

^{*}STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

Modulo Digaram



Dimensions in brackets are in inches.
Un-bracketed dimensions are in millimeters.
Unit: mm[in.]



Junction Box Top View(Lid Open)




Section A-A



Features

- Nominal 12V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

Characteristics



Polycrystalline silicon solar cell
72(4X18)
1500mm[59.06in.]x675mm[26.57in.]x35mm[1.38in.]
12.0kg[26.46lbs]
1540mm[60.63in.]x715mm[28.15in.]x85mm[3.35in.]/(2pcs/ctn)

^{*}Limited warranty: 5-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us. *Specifications are subject to change without notice at any time.

www.solarland.com info@solarland.com SOLARLAND 2012-2013

^{*}NOCT:Nominal operating cell temperature (the data is only for reference)